BMD51363 1/4



PRODUCT-DETAILS

BMD51363

BMD51363 Switch Disconnector



General Information	
Extended Product Type	BMD51363
Product ID	2CDD643051R0063
EAN	4016779038621
Catalog Description	BMD51363 Switch Disconnector
Long Description	The basic M switch disconnector is suitable for commanding loads according to IEC 60947-3.

Technical	
Standards	IEC 60947-3
Rated Voltage (U _r)	415 V 24 V Minimum
Rated Operational Voltage	415 V AC
Input Voltage Type	AC
Rated Current (In)	63 A
Rated Conditional Short- Circuit Current (I _{nc})	5 kA
Rated Service Short-	12 kA

BMD51363 2/4

Circuit Breaking	
Capacity (I _{cs})	

Rated Frequency (f)	50 / 60 Hz
Power Loss	at Rated Operating Conditions per Pole 5.03 W
Electrical Endurance	1500 AC cycle
Mechanical Endurance	8500 cycle
Number of Protected Poles	3
Number of Poles	3
Tightening Torque	2 N·m
Utilization Category	Switching of mixed resistive and inductive loads, including moderate overloads - frequent actuation (AC-22A)
Actuator Type	Toggle
Switch Type	Off
Actuator Marking	1/0
Recommended Screw Driver	Pozidriv 2
Accessories Available	No
Cover Color	Grey
Connecting Capacity	Flexible 25 mm² Rigid 35 mm²
Wire Stripping Length	12.5 mm
Terminal Type	Screw Terminals

Material Compliance

RoHS Information	2CDK400669D0201
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20170816
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
REACH Date	20231212
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air	Operation -25 +55 °C
Temperature	Storage -40 +70 °C
Degree of Protection	IP20
	Enclosure with Cover IP40

Dimensions

Width in Number of Modular Spacings	3
Product Net Width	52.5 mm
Product Net Height	69 mm
Product Net Depth / Length	88 mm
Product Net Weight	210 g
Built-In Depth (t ₂)	69 mm

BMD51363 3/4

Ordering	
Package Level 1 Units	4 piece
Package Level 1 Gross Weight	0.901 kg

Certificates and Declarations

Declaration of 2CDK400668D2701 Conformity - CE

Installation

Instructions and No document needed Manuals

Popular Downloads

Data Sheet, Technical 9AKK107045A1496 Information

Classifications

ETIM 8	EC001545 - Main switch for distribution board
ETIM 9	EC001545 - Main switch for distribution board
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 90 95
eClass	V11.0 : 27142301

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Basic\ M\ System \rightarrow Switch\ Disconnectors$

BMD51363 4/4

