



 PRODUCT-DETAILS

BMFW240/AC30

Residual Current Circuit Breaker - 2P - 40 A



General Information

Extended Product Type	BMFW240/AC30
Product ID	1SYF602062R1400
EAN	8906176431452
Catalog Description	Residual Current Circuit Breaker - 2P - 40 A
Long Description	The RCCB BMFW240/AC30 assures protection to people and installations against fault current to earth. This product is manufactured according to IEC Standards for the markets where it is required.

Technical

Rated Voltage (U_r)	230 V
Rated Impulse Withstand Voltage (U_{imp})	4 kV
Input Voltage Type	AC
Rated Current (I_n)	40 A
Rated Frequency (f)	50 Hz
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle

Number of Poles	2P
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Flexible 35 mm ² Flexible Solid;25 mm ²

Material Compliance

RoHS Status	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20

Dimensions

Product Net Width	35 mm
Product Net Height	88 mm
Product Net Depth / Length	74.25 mm
Product Net Weight	0.159 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	178 g

Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A0983
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK108469A0989
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108469A4847
-----------------------------------	-----------------

Classifications

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs

