

PRODUCT-DETAILS

## BMSW1C16

## Miniature Circuit Breaker - BMSW - 1P - 16 A - C



General Information		
Extended Product Type	BMSW1C16	
Product ID	1SYS651062R0164	
EAN	8906176430387	
Catalog Description	Miniature Circuit Breaker - BMSW - 1P - 16 A - C	
	The MCB 6kA BMSW1C16 provides overcurrent and short-cuicuit protection for	
Long Description	household and similar installations. This product is manufactured according to IEC Standards for the markets where it is required.	

Technical		
Tripping Characteristic	С	
Rated Voltage (U <sub>r</sub> )	230/400 V	
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV	
Rated Current (In)	16 A	
Rated Short-Circuit Capacity	6 kA	
Rated Frequency (f)	50/60 Hz	

BMSW1C16 2/3

Energy Limiting Class	3
Electrical Endurance	20000 cycle
Mechanical Endurance	20000 cycle
Number of Poles	
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Flexible 35 mm² Flexible Solid;25 mm²
Material Compliance	
RoHS Status	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental	_
Ambient Air Temperature	Operation -25 +55 °C
Degree of Protection	IP20
Pollution Degree	2
Dimensions	
Product Net Width	17.4 mm
Product Net Height	88.5 mm
Product Net Depth / Length	74.8 mm
Product Net Weight	0.096 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	104 g
Declaration of	9AKK108469A0980
Conformity - CE	
Popular Downloads	
Data Sheet, Technical Information	9AKK108469A4847
Classifications	
WEEE Category	Product Not in WEEE Scope

BMSW1C16 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Miniature\ Circuit\ Breakers\ MCBs \rightarrow Miniature\ Circuit\ Breakers\ MCBs$ 





