



PRODUCT-DETAILS

BMSW1C40**Miniature Circuit Breaker - BMSW - 1P - 40 A - C****General Information**

Extended Product Type	BMSW1C40
Product ID	1SYS651062R0404
EAN	8906176430424
Catalog Description	Miniature Circuit Breaker - BMSW - 1P - 40 A - C
Long Description	The MCB 6kA BMSW1C40 provides overcurrent and short-circuit protection for household and similar installations. This product is manufactured according to IEC Standards for the markets where it is required.

Technical

Tripping Characteristic	C
Rated Voltage (U _r)	230/400 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Current (I _n)	40 A
Rated Short-Circuit Capacity	6 kA
Rated Frequency (f)	50/60 Hz

Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle
Number of Poles	1P
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Flexible 35 mm ² Flexible Solid;25 mm ²

Material Compliance

RoHS Status	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C
Degree of Protection	IP20
Pollution Degree	2

Dimensions

Product Net Width	17.4 mm
Product Net Height	88.5 mm
Product Net Depth / Length	74.8 mm
Product Net Weight	0.111 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	119 g

Certificates and Declarations

Declaration of Conformity - CE	9AKK108469A0980
--------------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108469A4847
-----------------------------------	-----------------

Classifications

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

