E204/125R 1/3



PRODUCT-DETAILS

E204/125R

E204/125R Switch Disconnector



| General Information | |
|-----------------------|---|
| Extended Product Type | E204/125R |
| Product ID | 2CDE284001R0125 |
| EAN | 4016779646321 |
| Catalog Description | E204/125R Switch Disconnector |
| Long Description | These devices are suitable for commanding loads and they are realized according EN 60947-3 and EN 60669-1 respectively. Fast removal without dismantling of the busbar. Captive screws with recessed/slotted head. Pozidrive size 2. Add-on of up to 3 auxiliary contact S2C-H6R possible Integrated lay-on edge for labeling system ILS. Locking device as accessories for unauthorized ON/OFF. Approval: VDE, CCC, KEMA |

| Technical | |
|---------------------------------|-----------------------|
| Standards | IEC/EN 60947-3 |
| Rated Voltage (Ur) | 400 V 12 V Minimum |
| Rated Operational Voltage | 230 / 400 V AC |
| Input Voltage Type | AC |
| Rated Current (I _n) | 125 A |

E204/125R 2/3

| Rated Conditional Short- | 6 kA |
|-----------------------------|--|
| Circuit Current (Inc) | |
| Rated Service Short- | 6 kA |
| Circuit Breaking | |
| Capacity (I _{cs}) | |
| Power Loss | at Rated Operating Conditions per Pole 6.1 W |
| Number of Contacts CO | 0 |
| Number of Contacts NC | 0 |
| Number of Contacts NO | 4 |
| Number of Poles | 4 |
| Switch Type | Off |
| Recommended Screw | Pozidriv 2 |
| Driver | |
| Accessories Available | Yes |
| Cover Color | Grey |
| | |

| Material Compliance | |
|---|--|
| RoHS Information | 2CDK440002K0201 |
| RoHS Status | Following EU Directive 2011/65/EU |
| RoHS Date | 20110701 |
| REACH Declaration | 9AKK108468A9644 |
| REACH Information | False - does not contains substances > 0.1 mass percentage |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

| IP10 |
|------|
| |

| Dimensions | |
|--|---------|
| Width in Number of Modular Spacings | 4 |
| Product Net Width | 70 mm |
| Product Net Height | 85 mm |
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 0.39 kg |
| Built-In Depth (t ₂) | 70 mm |

| Ordering | |
|---------------------------------|----------------|
| Package Level 1 Units | carton 2 piece |
| Package Level 1 Gross Weight | 0.825 kg |

| Certificates and Declarations | |
|-------------------------------|-----------------|
| Certification Agency | EN |
| | IEC |
| Declaration of | 2CDK441011D0403 |
| Conformity - CE | |

E204/125R 3/3

| Installation | |
|------------------|-----------------|
| Instructions and | 2CSC400002D0208 |
| Manuals | |

| Popular Downloads | |
|-----------------------|-----------------|
| Data Sheet, Technical | 2CSC400002D0209 |
| Information | |

| Classifications | |
|-----------------------|--|
| ETIM 8 | EC001545 - Main switch for distribution board |
| ETIM 9 | EC001545 - Main switch for distribution board |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8536 50 80 |
| eClass | V11.0 : 27142301 |
| Object Classification | Q |
| Code | |

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Command\ and\ Signalling\ Devices\ \rightarrow\ Switch\ Disconnectors$





